

# QUALSTAR RLS-8350 EXPANDABLE RACKMOUNT TAPE LIBRARY

RELIABILITY,  
PERFORMANCE  
AND VALUE



The RLS-8350 extends Qualstar's well-respected RLS-8500 Series of *Simply Reliable* automated, high capacity rack mountable tape libraries. Delivering superior performance and value, the RLS-8350 provides 125 terabytes (native). Using typical data compression ratios, capacity can exceed 312 terabytes.

#### **EXPANSION READY**

Any RLS-8350 library can be expanded by adding an RLS-85120, tripling capacity and performance. The total configuration can support up to eight LTO 5 or LTO 6 SAS or fibre channel tape drives and up to 170 tapes, yielding over one petabyte in just 16U of rack space. FastPass™, the simple, robust tape mover installs in minutes and fits entirely within the library. Tapes are passed internally from one module to the next without impacting ongoing read/write operations. FastPass can be installed by an end user, and the expanded library is completely self-calibrating. No additional power or cooling is needed.

#### **ENCRYPTION ENABLED**

Protect valuable data in transit. The RLS-8350 enables use of the powerful AES 256-bit data encryption capability built into every LTO 5 tape drive. Simple,

easy-to-use, library-enabled encryption allows administrators to assign a separate key to the tapes in each partition.

#### **Q-LINK™ REMOTE MANAGER**

Q-Link is the web browser-based library manager that allows any RLS tape library to be configured, monitored, diagnosed and managed from anywhere in the world. Even firmware updates can be implemented remotely.

#### **RELIABLE, INTELLIGENT ROBOTICS**

The RLS-8350's unique robotic mechanism is *Simply Reliable* by design. Leadscrew based robotics using brushless DC motors and closed-loop servo control systems provide precise positioning. All FRUs, options and tape drives are auto-discovering, and all electrical and mechanical adjustments have been completely eliminated. Each tape drive is a self-connecting assembly, simply slide the drives in or out. All service access is through the front or rear of the unit.

#### **EASY OPERATION**

The RLS-8350 is equipped with a high resolution, color touch screen for local operation. An

intuitive menu-driven control system provides easy-to-use installation, configuration and operation information. All of the information, functions and controls built into the front panel display are replicated in Q-Link. If allowed by user security policies, Qualstar Technical Support can use Q-Link to monitor library operation to assist with configuration issues and troubleshooting.

#### **ADVANCED CARTRIDGE MANAGEMENT AND SECURITY**

Barcode scanning enhances throughput and controls the media inventory. RLS-8350 is equipped with a 4-slot I/O port for efficient media import and export.

#### **LOGICAL LIBRARY**

Logical Library partitioning is built into the RLS-8350 library. It allows up to three servers to share a single library, even if each server is running a separate application. Systems that weren't economical to upgrade can now be protected, automatically.



SIMPLY RELIABLE

# QUALSTAR RLS-8350 EXPANDABLE RACKMOUNT TAPE LIBRARY

RELIABILITY, PERFORMANCE AND VALUE



### ENGINEERED FOR RELIABILITY

- Auto-connecting, user-installable tape drives
- All brushless motors
- Self-calibrating all-digital servo control system
- Auto-aligning: no mechanical or electrical adjustments
- Auto-discovery of all components
- Over 2,000,000 MEBF
- Automated tape drive cleaning
- Filtered, forced-air cooling

### COMPREHENSIVE USER INTERFACE

- Q-Link browser-based remote library manager
- Color LCD touch control panel and menu system for easy installation, configuration, operation and maintenance

### VERSATILITY

- Expandable to 170 slots and 8 drives with FastPass™ tape mover option
- Library-enabled encryption
- ADI library interface
- N+1 power option
- SAS and Fibre Channel drive support
- Logical Library partitioning
- All access through front and back of unit

### EFFICIENT MEDIA CONTROL

- Barcode scanner
- 4-slot I/O port

### VALUE

- Three year warranty
- User field expandable
- Dedicated I/O port does not reduce capacity
- Simple, easy-to-use encryption
- Rack mount kit

RLS-8350 SERIES SPECIFICATIONS	RLS-8350	EXPANDABLE TO:
Drive Type	LTO 5 and LTO 6	
Number of Drives	1 – 3	Up to 8
Number of Data Tapes	50	104, 164 or 170
Native Capacity LTO 5 (TB)	75	Up to 255
Native Capacity LTO 6 (TB)	125	Up to 425
Hours of SD (25Mb) Video - LTO 5*	5,750	Up to 19,550
Hours of SD (25Mb) Video - LTO 6*	9,600	Up to 32,600
Max Compressed Capacity - LTO 5 (TB)*	150	Up to 510
Max Compressed Capacity - LTO 6 (TB)*	312	Over 1 PB
Max Native Data Rate - LTO 5 (TB/hr)	1.5	4
Max Compressed Data Rate - LTO 5 (TB/hr)*	3	8
Max Native Data Rate - LTO 6 (TB/hr)	1.7	4.4
Max Compressed Data Rate - LTO 6 (TB/hr)*	4.3	11.5
Library Interface	ADI	
Drive Interfaces	SAS, FC	
Average Exchange Time (seconds)	7.5	
FastPass Time (seconds)	< 2	
Time to Scan All Barcodes (seconds)	< 112	< 149
Barcode Reader	Standard	
Rack Mount Kit	Standard	
I/O Port / Slots	1 port with 4 slots	Up to 3 ports with 4 slots each
Height (in/cm)	6U (10.5 / 26.7)	16U (28 / 71.1)
Width (in/cm)	16.6 / 42.2	
Depth (in/cm)	35.3 / 89.7	
Net Weight (lb/kg)	166 / 75.3	388 / 176
Power Consumption (watts, avg)	85	170

\* Using typical compression ratios

**QUALSTAR CORPORATION**  
3990-B Heritage Oak Court  
Simi Valley, CA 93063

NASDAQ: QBAK

Fax: 805-583-7749  
Tel: 805-583-7744  
888-814-3975 Toll Free USA  
E-mail: sales@qualstar.com  
Website: www.qualstar.com

Qualstar Corporation does not warrant the MEBF to be representative of any particular unit installed for customer use. Failure rates are derived from a large database of test samples. The individual failure rate will vary from unit to unit.

All information and specifications are based on our knowledge of the products at the time of printing. Qualstar reserves the right to change specifications without notice.

Qualstar and the Qualstar logo are trademarks or registered trademarks of Qualstar Corporation.

LTO is a trademark of Hewlett-Packard, IBM and Quantum. All other trademarks are the property of their respective owners.

Qualstar products are covered by one or more of the following patents: 6,271,982, 6,560,061 and 7,181,313. Other patents pending.

Copyright © 2012 Qualstar Corporation. All rights reserved. Printed in USA DS 284 10/12



## SIMPLY RELIABLE